





T66201 / Louisiana




T66202 / Mississippi



T66203 / Texas




T66205 / Creole




T66204 / Cajun



T66206 / Everglade



T66207 / Wetlands



T66208 / Crawfish

Style	T662 "Bayou"
Construction	Hi / Mid / Lo Loop
Pile Fibre	nexlon™ Premium Solution Dyed Nylon featured with Quartz
Dye Method	Solution Dyed
Gauge	1 / 12G
Pile Height	5.5 / 4.5 / 3.0mm
Total Thickness	8.0mm(±0.5mm)
Tile size	500mm x 500mm
Total Weight	Approx. 5000g / m ²
Secondary Back	Recyclable TUNTEX Commercial Duraback

Wear Warranty	Product is warranted not to lose more than 10% pile fibre by weight in normal commercial use within 15 years.
Colour Fastness	15 Year Warranty AATCC 16, Grade 4 – Little or no change.
Static Electricity	Permanent Lifetime Protection – less than 2.0 KV.
Stain Resistance	Stainshield Treatment: STAINSHIELD™
Soil Resistance	Soil Guard Treatment: SOILGUARD™
Dimensional Stability	Warranted not to change in size by more than 0.5 mm in normal use. Will not dome or dish in normal use.
Installation	Tackifier or Releasable adhesive Recommended.
Sustainability	All yarns used are Solution dyed to minimise use of water and exclude any effluent production. ISO 14001 and ISO 9001.

Health Product Declaration (HPD) Third Party verified by U.S. GreenCircle Certified.

Environmental Product Declaration (EPD) certified by UL.

U.S. CRI Green Label Plus Certificate.

Singapore Green Building Council Product Certificate - 4 Ticks "Leader".

Passes ASTM Flammability Test.
Flammability: Passes (ASTM E648)
Smoke Density: Passes (ASTM E662)

Passes AATCC Static Propensity Test.
Static Propensity: ≤3.5 KV (AATCC 134)

Passes the Quality Test of China National Carpet Quality Test Center.

Passes the Flammability Test and Environmental Protection Test of the China National Fire and Construction Quality Surveillance Center.

ISO9001 Quality Management System.

ISO14001 Environmental Management System.

Passes EN 13501 European Fire Test Bfl.

Passes EN 1307 Wear Rating Class 33 - Heavy Commercial.





Color:T66204/T66206



Color:T66202

All images are computer generated files and may not exactly represent actual installation appearance and tile seams. Full tiles can be provided if required.







Color:T66207/T66208



Color:T66205