

















T717G "Sq Cloud"

Multi Hi / Lo Loop Construction

Pile Fibre nexlon™Premium Solution Dyed Nylon with Stain &

Soil Resist Technology

Solution Dyed

Gauge 1 / 10G

Tile size

Sustainability

Pile Height 4.0 - 2.5mm

8.4mm(±0.5mm) **Total Thickness**

Approx. 6250g / m²

RECYCLED TUNTEX Commercial Duraback Secondary Back

500mm x 500mm

Product is warranted not to lose more than 10% pile fibre by weight in normal commercial use within 15 years. **Wear Warranty**

Colour Fastness 15 Year Warranty AATCC 16. Grade 4 - Little or no change.

Permanent Lifetime Protection - less than 2.0 KV. Static Electricity

Stain Resistance Stainshield Treatment: STAINSHIELD™ Soil Resistance Soil Guard Treatment: SOILGUARD™ **Odor Reducer** Ecofresh Treatment: **ECO**FRESH™ **Anti-microbial** Microshield Treatment: MICROSHIELD™

Dimensional Stability Warranted not to change in size by more than 0.5 mm in normal use. Will not dome or dish in normal use.

Installation Tackifier or Releasable adhesive Recommended.

> All yarns used are Solution dyed to minimise use of water and exclude any effluent production. ISO 14001 and ISO 9001.

Health Product Declaration (HPD) Third Party verified by U.S. GreenCircle Certified.

Environmental Product Declaration (EPD) certified by UL.

U.S. CRI Green Label Plus Certificate.

Singapore Green Building Council Product Certificate - 4 Ticks "Leader".

Passes ASTM Flammability Test. Flammability: Passes (ASTM E648) Smoke Density: Passes (ASTM E662)

Passes AATCC Static Propensity Test. Static Propensity: ≤3.5 KV (AATCC 134)

Passes the Quality Test of China National Carpet Quality Test Center.

Passes the Flammability Test and Environmental Protection Test of the China National Fire and Construction Quality Surveillance Center.

ISO9001 Quality Management System.

ISO14001 Environmental Management System.

Passes EN 13501 European Fire Test Bfl.

Passes EN 1307 Wear Rating Class 33 - Heavy Commercial.

















TUNTEX[™]



All images are computer generated files and may not exactly represent actual installation appearance and tile seams.
Full tiles can be provided if required.

