




T81606 / T81608 / T10209 Herringbone

TUNTEX™



Immerse
T816





Style T816 "Immerse"

Construction Hi / Mid / Lo Loop

Pile Fibre nexlon™ Premium Solution Dyed Nylon featured with quartz

Dye Method Solution Dyed

Gauge 1 / 12G

Pile Height 5.5 / 4.5 / 3.0mm

Tile size 250mm x 1000mm

Secondary Back TUNTEX Duraback

Stain Resistance Stainshield Treatment: **STAINSHIELD™**

Soil Resistance Soil Guard Treatment: **SOILGUARD™**

Wear Warranty Product is warranted not to lose more than 10% pile fibre by weight in normal commercial use within 15 years.

Colour Fastness 15 Year Warranty AATCC 16. Grade 4 - Little or no change.

Static Electricity Permanent Lifetime Protection - less than 2.0 KV.

Dimensional Stability Warranted not to change in size by more than 0.5 mm in normal use. Will not dome or dish in normal use.

Installation Tackifier or Releasable adhesive Recommended.

Sustainability All yarns used are Solution dyed to minimise use of water and exclude any effluent production. ISO 14001 and ISO 9001.

Health Product Declaration (HPD) Third Party verified by U.S. GreenCircle Certified.

U.S. CRI Green Label Plus Certificate.

Singapore Green Building Council Product Certificate - 4 Ticks "Leader".

Passes ASTM Flammability Test.

Critical Radiant Flux: Passes (ASTM E648)

Smoke Density: Passes (ASTM E662)

Passes AATCC Static Propensity Test.

Electrostatic Propensity: Passes (AATCC 134)

Passes the Quality Test of China National Carpet Quality Test Center.

Passes the Flammability Test of the China National Fire and Construction Quality Surveillance Center.

ISO 9001 Quality Management System.

ISO 14001 Environmental Management System.

ISO 45001 Healthy & Safety Management System.



T81601 / T81609 Ashlar

Immerse

T816 product insight



T81601 / T81603 Ashlar



T81601 / T81606 Herringbone