



## Bouquet

LC08 Bouquet captures the beauty and brilliance of blooming flowers, and combined with LuxCushion™, Transforms each step into a sensation of strolling through a soft, sunlit pasture.













LC0803 Ashlar

LC0803 Ashlar



LC0803 Herringbone











LC0801 Ashlar





Bluebell

LC0802 Olive Leaf

LC0804

Blue Orchid



LC0803

LC0805

Daisy

Marigold

Wear Warranty Colour Fastness

Singapore Green Building Council Product Certificate - 4 Ticks "Leader".

Passes ASTM Flammability Test. Flammability: Passes (ASTM E648) Smoke Density: Passes (ASTM E662)

Passes the Quality Test of China National Carpet Quality Test Center.

Passes the Flammability Test and Environmental Protection Test of the China National Fire and Construction Quality Surveillance Center.

ISO 9001 Quality Management System.

ISO 45001 Healthy & Safety Management System.



Style	LC08 "Bouquet"
Construction	Multi Hi / Lo Loop
Pile Fibre	nexlon <sup>™</sup> Premium Solution Dyed Nylon
Dye Method	Solution Dyed
Gauge	1 / 10G
Pile Height	7.5 - 3.5mm
Total Thickness	13.5mm(±0.5mm)
Tile size	500mm x 1000mm
Total Weight	Approx. 3450g/m <sup>2</sup>
Secondary Back	<b>LUX</b> CUSHION™
Stain Resistance	Stainshield Treatment: STAINSHIELD"
Soil Resistance	Soil Guard Treatment: SOILGUARD
Odor Reducer	Ecofresh Treatment: ECOFRESH"
Anti-microbial	Microshield Treatment: MICROSHIELD"
Wear Warranty	Product is warranted not to lose more than 10% pile fibre by weight in normal commercial use within 15 years.
Colour Fastness	15 Year Warranty AATCC 16. Grade 4 - Little or no change.
Static Electricity	Permanent Lifetime Protection - less than 2.0 KV.
Dimensional Stability	Warranted not to change in size by more than 0.5 mm in normal use. Will not dome or dish in normal use.
Installation	Tackifier or Releasable adhesive Recommended.
Sustainability	All yarns used are Solution dyed to minimise use of water and exclude any effluent production. ISO 14001 and ISO 9001.

Health Product Declaration (HPD).

U.S. CRI Green Label Plus Certificate.

Passes AATCC Static Propensity Test. Static Propensity: ≤ 2.0 KV (AATCC 134)

ISO 14001 Environmental Management System.

