Sunshower T807



Sunshower

T807 Sunshower mimics the appearance of light raindrops while the sun is shining. This subtle natural phenomenon gives people a pleasant escape from reality for a moment.

















T80701 Cloud



T80704 Slate





T80706 Ash

T80708 Iron

Colour Fastness Static Electricity **Dimensional Sta**

Health Product De by U.S. GreenCircle Certified.

U.S. CRI Green Label Plus Certificate.

Passes ASTM Flammability Test. Flammability: Passes (ASTM E648) Smoke Density: Passes (ASTM E662)

Passes the Quality Test of China National Carpet Quality Test Center.

ISO 9001 Quality Management System.

ISO 14001 Environmental Management System.



T80701 / T80705 Ashlar

Style	T807 "Sunshower"
Construction	Hi / Mid / Lo Loop
Pile Fibre	nexlon [™] Premium Solution Dyed Nylon featured with aircell
Dye Method	Solution Dyed
Gauge	1 / 12G
Pile Height	5.5 / 4.5 / 3.0mm
Total Thickness	7.2mm(±0.5mm)
Tile size	250mm x 1000mm
Total Weight	Approx. 4950g / m ²
Secondary Back	TUNTEX Duraback
Stain Resistance	Stainshield Treatment: STAINSHIELD"
Soil Resistance	Soil Guard Treatment: SOILGUARD
Wear Warranty	Product is warranted not to lose more than 10% pile fibre by weight in normal commercial use within 15 years.
	Product is warranted not to lose more than 10% pile fibre by
Wear Warranty	Product is warranted not to lose more than 10% pile fibre by weight in normal commercial use within 15 years.
Wear Warranty Colour Fastness	Product is warranted not to lose more than 10% pile fibre by weight in normal commercial use within 15 years. 15 Year Warranty AATCC 16. Grade 4 - Little or no change.
Wear Warranty Colour Fastness Static Electricity	Product is warranted not to lose more than 10% pile fibre by weight in normal commercial use within 15 years. 15 Year Warranty AATCC 16. Grade 4 - Little or no change. Permanent Lifetime Protection - less than 2.0 KV. Warranted not to change in size by more than 0.5 mm in normal
Wear Warranty Colour Fastness Static Electricity Dimensional Stability	Product is warranted not to lose more than 10% pile fibre by weight in normal commercial use within 15 years. 15 Year Warranty AATCC 16. Grade 4 - Little or no change. Permanent Lifetime Protection - less than 2.0 KV. Warranted not to change in size by more than 0.5 mm in normal use. Will not dome or dish in normal use.

Singapore Green Building Council Product Certificate - 4 Ticks "Leader".

Passes AATCC Static Propensity Test. Static Propensity: ≤ 2.0 KV (AATCC 134)

Passes the Flammability Test and Environmental Protection Test of the China National Fire and Construction Quality Surveillance Center.

ISO 45001 Healthy & Safety Management System.

