

To grant and the

TUNTE











T66201 Quarter-Turn







T66202 Quarter-Turn



T66202 / T66203 / T66206 Quarter-Turn


















T66205 Creole











T66207 Wetlands



T66208 Crawfish













Style	T662 "Pick Up Sticks"
Construction	Hi / Mid / Lo Loop
Pile Fibre	nexlon [™] Premium Solution Dyed Nylon featured with quartz
Dye Method	Solution Dyed
Gauge	1 / 12G
Pile Height	5.5 / 4.5 / 3.0mm
Total Thickness	8.0mm(±0.5mm)
Tile size	500mm x 500mm
Total Weight	Approx. 5000g/m ²
Secondary Back	TUNTEX Duraback
Stain Resistance	Stainshield Treatment: STAINSHIELD"
Soil Resistance	Soil Guard Treatment: SOILGUARD"
Soil Resistance	Soil Guard Treatment: SOILGUARD"
Soil Resistance Wear Warranty	
	Product is warranted not to lose more than 10% pile fibre by
Wear Warranty	Product is warranted not to lose more than 10% pile fibre by weight in normal commercial use within 15 years.
Wear Warranty Colour Fastness	Product is warranted not to lose more than 10% pile fibre by weight in normal commercial use within 15 years. 15 Year Warranty AATCC 16. Grade 4 - Little or no change.
Wear Warranty Colour Fastness Static Electricity	Product is warranted not to lose more than 10% pile fibre by weight in normal commercial use within 15 years. 15 Year Warranty AATCC 16. Grade 4 - Little or no change. Permanent Lifetime Protection - less than 2.0 KV. Warranted not to change in size by more than 0.5 mm in normal
Wear Warranty Colour Fastness Static Electricity Dimensional Stability	Product is warranted not to lose more than 10% pile fibre by weight in normal commercial use within 15 years. 15 Year Warranty AATCC 16. Grade 4 - Little or no change. Permanent Lifetime Protection - less than 2.0 KV. Warranted not to change in size by more than 0.5 mm in normal use. Will not dome or dish in normal use.

Health Product Declaration (HPD).

U.S. CRI Green Label Plus Certificate.

Singapore Green Building Council Product Certificate - 4 Ticks "Leader".

Passes ASTM Flammability Test. Flammability: Passes (ASTM E648) Smoke Density: Passes (ASTM E662)

Passes AATCC Static Propensity Test. Static Propensity: ≤ 2.0 KV (AATCC 134)

Passes the Quality Test of China National Carpet Quality Test Center.

Passes the Flammability Test and Environmental Protection Test of the China National Fire and Construction Quality Surveillance Center.

ISO 9001 Quality Management System.

ISO 14001 Environmental Management System.

ISO 45001 Healthy & Safety Management System.



