



# Velvet Care

T909

TUNTEX™

# Velvet Care

T909 Velvet Care translates the richness of silk velvet into a textile language. The style pairs a cut-pile finish with a muted palette to deliver a grounded, premium aesthetic for contemporary environments.





T90902 Ashlar



T90903 / T90905 Ashlar



T90906 Ashlar



T90903 / T90906 Ashlar






T90905 Herringbone









T90902 Mist




T90903 Haze



T90904 Moss




T90905 Amber



T90906 Lake



T90907 Fern



T90909 Mauve

<b>Style</b>	T909 "Velvet Care"
<b>Construction</b>	High Cut Mid / Low Loop
<b>Pile Fibre</b>	nexlon™ Premium Solution Dyed Nylon
<b>Dye Method</b>	Solution Dyed
<b>Gauge</b>	1/10 G
<b>Pile Height</b>	6.0/5.0/3.8 mm
<b>Total Thickness</b>	8.5 mm (±0.5 mm)
<b>Tile size</b>	250 mm x 1000 mm
<b>Total Weight</b>	Approx. 5250 g/m <sup>2</sup>
<b>Secondary Back</b>	TUNTEX Duraback
<b>Stain Resistance</b>	Stainshield Treatment: <b>STAINSHIELD™</b>
<b>Soil Resistance</b>	Soil Guard Treatment: <b>SOILGUARD™</b>

<b>Wear Warranty</b>	Product is warranted not to lose more than 10% pile fibre by weight in normal commercial use within 15 years.
<b>Colour Fastness</b>	15 Year Warranty AATCC 16. Grade 4 - Little or no change.
<b>Static Electricity</b>	Permanent Lifetime Protection - less than 2.3 KV.
<b>Dimensional Stability</b>	Warranted not to change in size by more than 0.5 mm in normal use. Will not dome or dish in normal use.
<b>Installation</b>	Tackifier or Releasable adhesive Recommended.
<b>Sustainability</b>	All yarns used are Solution dyed to minimise use of water and exclude any effluent production. ISO 14001 and ISO 9001.

Health Product Declaration (HPD) Third Party verified by U.S. GreenCircle Certified.

U.S. CRI Green Label Plus Certificate.

Singapore Green Building Council Product Certificate - 4 Ticks "Leader".

Passes ASTM Flammability Test.  
Flammability: Passes (ASTM E648)  
Smoke Density: Passes (ASTM E662)

Passes AATCC Static Propensity Test.  
Static Propensity: ≤ 2.3 KV (AATCC 134)

Passes the Quality Test of China National Carpet Quality Test Center.

Passes the Flammability Test and Environmental Protection Test of the China National Fire and Construction Quality Surveillance Center.

ISO 9001 Quality Management System.

ISO 14001 Environmental Management System.

ISO 45001 Healthy & Safety Management System.



