

# First Sprout LA15

# First Sprout



Inspired by the quiet renewal of an early spring garden, LA15 First Sprout sets the stage with seven understated shades, defining the essence of modern luxury. Designed for spaces that value minimalism and inner peace, it serves as a soft architectural retreat from the urban rush.



Designed for Stillness



LA1506 Ashlar

*Breathe in*



LA1503 Ashlar



LA1501 Ashlar



LA1502 Ashlar



LA1505 Ashlar



LA1504 Ashlar



LA1501 Ashlar



Layered Texture

LA1502 Ashlar





LA1503 Ashlar

Quiet Renewal



LA1506 Ashlar




# A Gentle Return




LA1501  
Cloud



LA1502  
Warm Soil



LA1503  
Fog



LA1504  
Morning Haze



LA1505  
Clear Sky



LA1506  
Pale Green



LA1507  
Fresh Green

<b>Style</b>	LA15 "First Sprout"
<b>Construction</b>	Multi Hi / Lo Loop
<b>Pile Fibre</b>	nexlon™ Premium Solution Dyed Nylon featured with aircell
<b>Dye Method</b>	Solution Dyed
<b>Gauge</b>	1/10 G
<b>Pile Height</b>	8.0-3.5 mm
<b>Total Thickness</b>	11.8 mm (±0.5 mm)
<b>Tile size</b>	500 mm × 1000 mm
<b>Total Weight</b>	Approx. 3350 g/m <sup>2</sup>
<b>Secondary Back</b>	LUXCUSHION™
<b>Stain Resistance</b>	Stainshield Treatment: <b>STAINSHIELD™</b>
<b>Soil Resistance</b>	Soil Guard Treatment: <b>SOILGUARD™</b>
<b>Odor Reducer</b>	Ecofresh Treatment: <b>ECOFRESH™</b>
<b>Anti-microbial</b>	Microshield Treatment: <b>MICROSHIELD™</b>

<b>Wear Warranty</b>	Product is warranted not to lose more than 10% pile fibre by weight in normal commercial use within 15 years.
<b>Colour Fastness</b>	15 Year Warranty AATCC 16. Grade 4 - Little or no change.
<b>Static Electricity</b>	Permanent Lifetime Protection - less than 2.0 kV.
<b>Dimensional Stability</b>	Warranted not to change in size by more than 0.5 mm in normal use. Will not dome or dish in normal use.
<b>Installation</b>	Tackifier or Releasable adhesive Recommended.
<b>Sustainability</b>	All yarns used are Solution dyed to minimise use of water and exclude any effluent production. ISO 14001 and ISO 9001.

Health Product Declaration (HPD).

U.S. CRI Green Label Plus Certificate.

Singapore Green Building Council Product Certificate - 4 Ticks "Leader".

Passes ASTM Flammability Test.  
Flammability: Passes (ASTM E648)  
Smoke Density: Passes (ASTM E662)

Passes AATCC Static Propensity Test.  
Static Propensity: ≤ 2.0 kV (AATCC 134)

Passes the Quality Test of China National Carpet Quality Test Center.

Passes the Flammability Test and Environmental Protection Test of the China National Fire and Construction Quality Surveillance Center.

ISO 9001 Quality Management System.

ISO 14001 Environmental Management System.

ISO 45001 Healthy & Safety Management System.



